



Scan to Visit the Superheat Website



SUPERHEAT™ SMARTLINK

Linking The Power of Blue

Introducing the Superheat SmartLink™ in Conjunction with Miller ProHeat™ 35:

Your gateway to knowledge and comprehensive digital management, providing solutions to address your induction heating challenges.

Key SmartLink™ Solutions:

Effortlessly program your Miller ProHeat™ 35 unit using the Superheat SmartLink™ interface while it digitally archives data for easy integration into your Quality Management System.

Access a library of eng. drawings to efficiently execute your procedural requirements, optimizing set-up configurations from the start.

Technical video mentoring and direct online communication for rapid support & assistance.

Why Induction Equipment?

Maintain control over schedule and cost without reliance on third-party heat treatment contractors. Empower your existing skilled trades.

Accelerated time-to-temperature through efficient heat application, reducing overall schedule attributed to heat treatment.



Superheat SmartView™ User Interface



Transform data into actionable insights, empowering informed decision-making. Superheat SmartView™ offers real-time status notifications, live heat cycle chart monitoring, and more, from the palm of your hand.



Enhance working conditions for welders by eliminating exposure to open flame, explosive gases, and hot elements.

Transfer more direct power draw to the component, creating an efficient system that decreases overall energy usage with less than a 60-amp current draw per unit.

Miller ProHeat™ 35 Specs:

Input Power	Rated Output	Input Amperes at Rated Output	Dimensions	Weight
460-575 V, 3-Phase, 60 Hz	35 kW at 100% Duty Cycle	50 A, 460 V 40 A, 575 V	H: 27.5" (699 mm) W: 21.75" (552 mm) D: 36.75" (933 mm)	Net: 227 lb (103 kg) Ship: 265 lb (120kg)
400-460 V, 3-Phase, 50/60 Hz		60 A, 400 V 50 A, 460 V		

BETTER SAFER FASTER™

superheat.com/smartlinkinduction • 888.508.3226 • sales@superheat.com